

TPWLK "LOGISTIC" SERIES PALLET TRUCK SCALE



TPWLK with extractable battery pack option.

Pallet truck scales, with built-in electronic weighing, which are reliable, easy to use, suitable for harsh work conditions. These are essential for one who needs to weigh accurately but save time also. Optional rechargeable extractable battery for continuous use. Available also with a built-in printer as well as CE-M DOUBLE RANGE approved.

MAIN FEATURES

- Maximum lifting capacity: 2000 kg.
- Accuracy: +/- 0.1% of the capacity.
- Fork dimensions 1170 x 550 x 85 mm.
- Weighs about 125 kg.
- Structure in extra thick steel and oven-fire painted mechanics.
- Steering wheels and double loading poliurethane rollers.
- 4 shear-beam load cells.
- Weight indicator in **STAINLESS STEEL IP68 waterproof case**, which is easy to clean and resistant to harsh and corrosive environments; **large 25mm LCD display** high contrast digits, which are clearly visible even in poor lighting conditions and with low temperatures, and waterproof membrane keyboard, with 17 functional keys.
- **Configuration, calibration and diagnostics from keyboard or PC with DINITOOLS.**
- Power supply through built-in rechargeable battery.
- The operating time is of about 80 hours of continuous use or one month with the tipycal non continuous use, thanks to its auto switch-off function.
- Programmable auto power saving function.
- Battery level indication.
- Equipped with 230Vac 50 Hz battery charger (recharging time is about 8 hours).
- Configurable RS232/C bidirectional port for **connection to a printer, with customisable print format.**
- Configurable RS232/C bidirectional port for PC, modem radio or portable terminal.
- IR input for remote control management.

OPTIONS ONLY AVAILABLE AT TIME OF ORDER

- Extractable rechargeable battery.
- Thermal/Virtual printer with Memory Card.
- Modem radio option box / WI-FI interface.
- Alibi memory with time-date
- Time-Date
- 2 inputs + 2 outputs configurable on gross or net weight.
- Stainless steel forks / Parking brake.
- 680 mm fork width (upon price estimate).
- Special fork length from 850 to 1500 mm (upon price estimate).
- Version with capacities and/or special divisions or high resolution (upon price estimate).

SELECTABLE FUNCTIONS

- **High Resolution Weighing x 10**
- **Net/Gross or lb/kg conversion**
- **Accumulation**
- **Formulation**
- **+/- Checkweighing**
- **Percentage weighing**
- **Counting**
- **In/Out Truck weighing**
- **Hold and Peak**
- **Peer-to-peer** (up to 4 remote connectable indicators)
- **Set Point Control** (with optional interface)

KEYBOARD FUNCTIONS AND PRINTOUT

- **KEYBOARD:** Zeroing, Automatic tare, Presettable tare, Print and/or data transmission command, Function command.
- **PRINTOUT:** configurable layout with:
3 header rows, net weight, gross weight, tare weight or weight totalized and total weigh, time/date, ticket number, weigh nr.

Versions available

Code	Max Capacity kg	Division kg	CE-M Division kg
TPWLK	500 / 1000 / 2000	0,2 / 0,5 / 1	
TPWLKM	1000 / 2000		0,5 / 1

Options only available at time of order

Code	Description
TPWXFI	Pair of stainless steel forks.
TPRPL	Thermal printer with >50mm/sec. speed, 203 dpi resolution, 24/40 columns, 58 mm width; 50 mm roll diameter.
CNFSERV	Configuration and printout customisation on DFW series' indicators (functioning mode and print heading) on OBTPR and LP542S - NET PRICE
RFITR	Integrated radio interface complete of RS232 port. Max. functioning distance in appropriate environmental and installation conditions : 70m indoors, 150m outdoors. Up to 50 configurable channels. (Must be combined with another radio modem)
DFCLK	Real Time Clock (Time/date)
DFIO	Module of 2 optoisolated digital inputs + 2 Photomosfet outputs usable as programmable weight threshold setpoints (not combinable with alibi memory ALMEM)
OBRFUSB	868MHz radio frequency module for PC with USB input, selfpowered, connectable to USB ports. Fitted with USB connection cable. Max. functioning distance in appropriate conditions: 70m indoor, 150m outdoor. 50 available channels, easily programmable from the PC.
OBRF232	868 MHz radio frequency module for PC with RS232 9-pole input, connectable to RS232 ports. Fitted with connection/power supply cable. Max. functioning distance in appropriate conditions: 70m indoors, 150m outdoors. 50 available channels, easily programmable from PC.
ALMEM	Alibi memory (fiscal memory) with time/date; max. 120.000 weighs
WIFIT	WI-FI interface for wireless connection (through access point) to the company computer system.
TPWFRE	Parking brake system with command pedal mounted on steering wheels
TPWLBK	Extractable backup battery kit
TPWBKB	Additional rechargeable battery for Backup Battery Kit.
TPWLBKPT	Backup battery kit and thermal printer for TPW pallet truck scales

Accessories

Code	Description
UKPLUG	Power adapter from Schuko to BS1363.
TECMAN	Printed technical manual (free, if downloaded from the web) NET PRICE
UMAN	Printed user manual (free, if downloaded from the web) NET PRICE